

Bottle filler and drinking fountain with silver powder-coated finish & pedestal, freeze-resistant

FEATURES & BENEFITS

PUSH BUTTON

Polished chrome-plated push-button requires less than 5 lbs. (2.7 kg) of push force to activate.

DRAIN CLEAN-OUT

Top-down access to the drain allows the fountain to be cleaned without taking the unit apart, good for outdoor settings with drain-clogging sediment such as leaves, garbage, and other debris.

FREEZE-RESISTANT VALVE

Fully engineered system with the pneumatic-operated, freeze-resistant valve mounted in a cabinet that is installed on the inside wall where room temperature does not drop below 50° F (10° C). When valve goes to off position, water left in supply line between valve and bubbler drains back into waste inside cabinet, protecting the unit from freezing, and allowing fountain to function year-round.

BARRIER-FREE

Barrier-free capabilities combined with its ease of use allows for a number of installation location possibilities.



SPECIFICATIONS

Model 3621FR modular outdoor, barrier-free, freeze-resistant pedestal bottle filler and drinking fountain shall include a 3/16" steel pedestal with phosphating and silver powder-coating, two bottle filling stations and one fountain, fully engineered pneumatic valve assemblies, large-opening bottle filler with quick-fill 1 gpm flow rate, polished chrome-plated brass vandal-resistant shielded bubbler head, 100% lead-free waterways, polished chrome-plated vandal-resistant fountain waste strainer with top-down clean-out access on fountain, vandal-resistant access plates, integral mounting feet, and 1-1/2" slip waste. REQUIRES MODELS 6518.2FR and 6518FR PRICED SEPARATELY.

OPTIONS

- Mounting System: Model MTG.3501, galvanized steel anchors.
- Dog Bowl, Freeze Resistant ODBF: Model 3670FR, freeze-resistant dog bowl for the 3600 series modular outdoor pedestals. Available in three standard colors - order 3670FR-01 silver, 3670FR-02 blue, and 3670FR-03 green.

APPLICATIONS

The 3621FR offers a solution for the changing needs of outdoor settings as well as outdoor wheelchair access, appealing to all users through accessibility and safety. This product is ideal in areas such as parks, schools, and other outdoor areas where hydration facilities are needed. Model meets all current Federal Regulations for the disabled including those in the Americans with Disabilities Act, and complies with Prop 65. Certified by CSA to NSF/ANSI 61, section 9 and NSF/ANSI 372; and was evaluated to be compliant to US and Canada Plumbing Codes including Uniform Plumbing Code (UPC), International Plumbing Code (IPC) and National Plumbing Code of Canada (NPC).

Postadress:

TRÄDGÅRDSTEKNIK AB
Helsingborgsvägen 578, Varalöv
262 96 ÄNGELHOLM

Telefon : 0431-222 90
Bg.nr : 5743-7980
Org.nr : 556409-6120

URL:

www.tradgardsteknik.se
E-postadress:
info@tradgardsteknik.se


